

EX22



Compactor ex22 for excavators 3-10 tons

TECHNICAL DATA:

Machine weight: 3-10 tons
vibration force: 2.2 tons
Vibration frequency: 33 Hz
Weight: 190 kg
length: 780 mm
Width: 450 mm
Height: 600 mm
holds: S30 / S40 / S45 / S50 etc.
Working pressure: 150 bar
My hydr. feed: 20/45 L / min
Max hydr. flow: 250 l / min
Maximum load pressure: 210 bar

Product Description:

The machine-mounted compactors facilitates compression in hard to reach areas and improves safety by eg compression in ditches / pits, when no one needs to stay in the work area.

The compactors is excellent for piling, for example, posts and partitions.

Slopes compressed easier to machine-mounted compactors.

The compactors can handle high back pressure on the return line, a characteristic that makes the most appropriate for use with rotortilt.

www.jels-es.dk



Jels Entreprenør
service

EX34



TECHNICAL DATA:

Machine Weight: 210 kg
Length: 805 mm
Width: 525 mm
Height: 600 mm
Vibration force: 3.4 tons
Vibration frequency: 33 Hz
Working pressure: 150 bar
My hydr. flow rate: 31 l / min
Max hydr. flow rate: 250 l / min
Max pressure load: 210 bar

www.jels-es.dk



Jels Entreprenør
service

EX41



TECHNICAL DATA:

Machine Weight: 10-20 tonnes
Compaction force: 4.1 tons
Weight: 380 kg
Length: 1,040 mm
Width: 610/680 mm
Height: 750mm
mountings: S45, S50, S60, S70, S1, S2, S45 OilQuick, 60, 70th
my hydr. Flow: 45l / min
Max hydr. Flow rate: 250l / min
Max pressure: 210 bar

Product Description:

The machine-mounted compactors facilitates compression in hard to reach areas and improves safety by eg compression in ditches / pits, when no one needs to stay in the work area.

The compactors is excellent for piling, for example, posts and partitions.

Slopes compressed easier to machine-mounted compactors.

The compactors can handle high back pressure on the return line, a characteristic that makes the most appropriate for use with rotortilt.

Also supplied as standard with OilQuick directly from the factory.

www.jels-es.dk



Jels Entreprenør
service

EX65



Compactor, 65 for excavators 20-30 tons

TECHNICAL DATA:

Machine Weight: 20-30 tonnes
Compaction Force: 6.5 tonnes
weight: 475 kg
Length: 1,040 mm
Width: 750 mm
Height: 750 mm
mountings: S60, S70, S1, S2, S60 OilQuick, 70.
My hydr. Flow: 70l / min
Max hydr. Flow rate: 250l / min
Max pressure: 210 bar

Product Description:

The machine-mounted compactors facilitates compression in hard to reach areas and improves safety by eg compression in ditches / pits, when no one needs to stay in the work area.

The compactors is excellent for piling, for example, posts and partitions.

Slopes compressed easier to machine-mounted compactors.

The compactors can handle high back pressure on the return line, a characteristic that makes the most appropriate for use with rotortilt.

Also supplied as standard with OilQuick directly from the factory.

www.jels-es.dk



Jels Entreprenør
service